



See page 36 for details

# UP50-W

50 mm Ø, 5 mW – 85 W, 100 kW/cm<sup>2</sup>



## KEY FEATURES

- 1. MODULAR CONCEPT**  
Increase the power capability of your detector:  
4 different cooling modules
- 2. VERY HIGH DAMAGE THRESHOLD**  
100 kW/cm<sup>2</sup> in average power density
- 3. VERY LARGE APERTURE**  
50 mm Ø effective aperture, perfect for the  
largest beams
- 4. HIGHEST ENERGY READINGS IN THE SERIES**  
Measure single shot energy up to 500 J
- 5. SMART INTERFACE**  
Containing all the calibration data

## AVAILABLE MODELS



UP50N-40S-W9  
(40W-Standalone)



UP50N-50H-W9  
(50W-Heatsink)



UP50N-50F-W9  
(50W-Fan-Cooled)



UP50M-50W-W9  
(50W-Water-Cooled)

## ACCESSORIES



Stand with Steel Post  
(Model Number: 200234)



Extension Cables  
(4, 15, 20 or 25 m)



Fiber Adaptors and Connectors  
(FC, SC or SMA)



3-Port Fiber Cylinder with  
Adaptors and Plug



12V Power Supply  
(Model Number: 200130)



Pelican Carrying Case

## SEE ALSO

|                                                                  |                        |
|------------------------------------------------------------------|------------------------|
| HOW IT WORKS                                                     | 14                     |
| CALIBRATION                                                      | 6                      |
| TECHNICAL DRAWINGS                                               | 86                     |
| ABSORPTION CURVES                                                | 90                     |
| OEM DETECTORS                                                    | 130                    |
| COMPATIBLE MONITORS                                              |                        |
| MAESTRO                                                          | 20                     |
| TUNER                                                            | 24                     |
| UNO                                                              | 26                     |
| S-LINK                                                           | 28                     |
| P-LINK                                                           | 30                     |
| M-LINK                                                           | 32                     |
| LISTE DES ACCESSOIRES                                            | 190                    |
| APPLICATION NOTE                                                 |                        |
| MEASURING LASER POWER WITH A<br>THERMOPILE DETECTOR: THE BASICS! | <a href="#">202175</a> |
| MEASURING HIGH POWER WITH A LOW<br>POWER DETECTOR                | <a href="#">202188</a> |

# UP50-W

## SPECIFICATIONS



\*Also traceable to NRC-CNRC

|                                                  | UP50N-40S-W9           | UP50N-50H-W9           | UP50N-50F-W9           | UP50M-50W-W9                          |
|--------------------------------------------------|------------------------|------------------------|------------------------|---------------------------------------|
| <b>MAX AVERAGE POWER (CONTINUOUS / 1 MINUTE)</b> | 40 W / 80 W            | 50 W / 85 W            | 50 W / 85 W            | 50 W <sup>f</sup> / 85 W <sup>f</sup> |
| <b>EFFECTIVE APERTURE</b>                        | 50 mm Ø                | 50 mm Ø                | 50 mm Ø                | 50 mm Ø                               |
| <b>COOLING METHOD</b>                            | Convection             | Heatsink               | Fan-Cooled             | Water-Cooled                          |
| <b>MEASUREMENT CAPABILITY</b>                    |                        |                        |                        |                                       |
| Spectral Range *                                 | 0.19 – 10 µm           | 0.19 – 10 µm           | 0.19 – 10 µm           | 0.19 – 10 µm                          |
| Noise Equivalent Power <sup>a</sup>              | 5 mW                   | 5 mW                   | 5 mW                   | 5 mW                                  |
| Rise Time (nominal) <sup>b</sup>                 | 3.5 sec                | 3.5 sec                | 3.5 sec                | 3.5 sec                               |
| Sensitivity (typ into 100 kΩ load) <sup>c</sup>  | 0.12 mV/W              | 0.12 mV/W              | 0.12 mV/W              | 0.12 mV/W                             |
| Calibration Uncertainty <sup>d</sup>             | ±2.5%                  | ±2.5%                  | ±2.5%                  | ±2.5%                                 |
| Repeatability                                    | ±0.5%                  | ±0.5%                  | ±0.5%                  | ±0.5%                                 |
| Energy Mode                                      |                        |                        |                        |                                       |
| Sensitivity                                      | 0.02 mV/J              | 0.02 mV/J              | 0.02 mV/J              | 0.02 mV/J                             |
| Maximum Measurable Energy <sup>e</sup>           | 500 J                  | 500 J                  | 500 J                  | 500 J                                 |
| Noise Equivalent Energy <sup>a</sup>             | 0.25 J                 | 0.25 J                 | 0.25 J                 | 0.25 J                                |
| Minimum Repetition Period                        | 11.1 sec               | 11.1 sec               | 11.1 sec               | 11.1 sec                              |
| Maximum Pulse Width                              | 467 ms                 | 467 ms                 | 467 ms                 | 467 ms                                |
| Accuracy with energy calibration option          | ±5%                    | ±5%                    | ±5%                    | ±5%                                   |
| <b>DAMAGE THRESHOLDS</b>                         |                        |                        |                        |                                       |
| Maximum Average Power Density <sup>g</sup>       | 100 kW/cm <sup>2</sup> | 100 kW/cm <sup>2</sup> | 100 kW/cm <sup>2</sup> | 100 kW/cm <sup>2</sup>                |
| Pulsed Laser Damage Thresholds                   | Max Energy Density     |                        | Peak Power Density     |                                       |
| 1064 nm, 150 µs, 5 Hz                            | 100 J/cm <sup>2</sup>  |                        | 667 kW/cm <sup>2</sup> |                                       |
| 1064 nm, 7 ns, 10 Hz                             | 1.1 J/cm <sup>2</sup>  |                        | 157 MW/cm <sup>2</sup> |                                       |
| 532 nm, 7 ns, 10 Hz                              | 1.1 J/cm <sup>2</sup>  |                        | 157 MW/cm <sup>2</sup> |                                       |
| 248 nm, 26 ns, 10 Hz                             | 0.7 J/cm <sup>2</sup>  |                        | 27 MW/cm <sup>2</sup>  |                                       |
| <b>PHYSICAL CHARACTERISTICS</b>                  |                        |                        |                        |                                       |
| Effective Aperture                               | 50 mm Ø                | 50 mm Ø                | 50 mm Ø                | 50 mm Ø                               |
| Absorber (High Damage Threshold)                 | W9                     | W9                     | W9                     | W9                                    |
| Dimensions                                       | 89H x 89W x 32D mm     | 89H x 89W x 106D mm    | 89H x 89W x 116D mm    | 89H x 89W x 40D mm                    |
| Weight (head only)                               | 0.62 g                 | 0.93 g                 | 1.38 g                 | 0.81 g                                |
| <b>ORDERING INFORMATION</b>                      |                        |                        |                        |                                       |
| Product Name                                     | UP50N-40S-W9           | UP50N-50H-W9           | UP50N-50F-W9           | UP50M-50W-W9                          |
| Product Number (Including stand)                 | 200896                 | 200897                 | 200898                 | 201887                                |
| Add Extension for INTEGRA                        | -INT                   | -INT                   | -INT                   | -INT                                  |

\* For the calibrated spectral range, see the user manual.

a. Nominal value, actual value depends on electrical noise in the measurement system.

b. With Gentec-EO MAESTRO, UNO, P-LINK, TUNER and S-LINK monitors.

c. Maximum output voltage = sensitivity x maximum power.

d. Including linearity with power.

e. For 360 µs pulses. Higher pulse energy possible when customized for long pulses (ms), less for short pulses (ns).

f. Minimum cooling flow 0.5 liters/min, water temperature ≤ 22°C, 1/8 NPT compression fittings for 1/4 inch semi-rigid tube.

Contact Gentec-EO for clean deionized water cooling module option.

g. At 1064 nm, 10 W CW.

Specifications are subject to change without notice