BEAM DIAGNOSTICS SPECIAL PRODUCTS OF

UNO

Single Channel, Power Monitor



NOW AVAILABLE



You can now toggle your display between Watts or dBm units

KEY FEATURES

1. READS ALL POWER DETECTORS

Thermopiles and photo detectors of the PH Series

2. LARGE LCD DISPLAY

- 76 x 57 mm
- 32 mm digits

3. UNIQUE ERGONOMIC DESIGN

Great for both handheld and tabletop use

4. ACCURATE

24 bit A/D converter for high resolution measurements

5. SINGLE-BUTTON NAVIGATION

Direct access and long press access to all the functions

6. EXTREMELY LOW CONSUMPTION

Lasts 670 hours with 4 AA alkaline batteries

7. ECONOMICAL

Get the best value for your money with this inexpensive and simple to use power monitor

ACCESSORIES



Optional 9V Power Supply (Model Number: 200960)



Wall Support (Model Number: 201241)



Protective Pouch (Model Number: 200128)

SEE ALSO

POWER DETECTORS	58
HIGH POWER DETECTORS	92
PHOTO DETECTORS	104
THZ DETECTORS	114
OEM DETECTORS	130
LIST OF ALL ACCESSORIES	190





UNO SPECIFICATIONS

	UNO
DETECTOR TYPES	Thermopiles, Photo Detectors (PH Series)
DISPLAY	LCD
POWER METER SPECIFICATIONS	
Power Range	5 pW to 10 kW
Thermopile	Autoscale
Photo Detector	Autoscale
Monitor Accuracy	±1 %
Statistics	None
DETECTOR COMPATIBILITY	
Thermopiles	Average Power (W, dBm)
Photo Detectors	Average Power (W, dBm)
GENERAL SPECIFICATIONS	
Digital Display Size	76 x 57 mm LCD
Digit Height	32 mm
Digit Type	High Contrast Fields
Data Display	Real Time
Dimensions (Without Stand)	210W x 122H x 44D mm
Weight (With Batteries)	0.47 kg
Battery Type	4 x AA Alkaline
Battery Life (Estimated)	670 hours with detector
External Power Supply (Optional)	100/240 VAC 50-60 Hz to 9 VDC 1.66 A
ORDERING INFORMATION	

Specifications are subject to change without notice

UNO

200982

Product Name

Product Number